



ToteGlass®
You'll Notice the Difference!

Tapping Device

Tote's Tapping Device Installation Instructions

Our tapping device features an adjustable on/off valve and hand squeeze pump to gently add pressure to the top of the beer, causing it to flow out through the stainless faucet without adding damaging oxygen to the beer or stirring up sediments.

The following steps will help you install a tapping device flawlessly every time.



1
Insert the hose into the growler. The hose will relax and fall to the bottom of the growler. You can help it along by submerging it in hot tap water beforehand.



2
Position the lower clip under the lid's porcelain hinge. Check to ensure the rubber gasket is equally seated on the growler's mouth.



3
Gently clip the tapping device down using the flip-top clip. Start with the tapping device's clip position closest to the body.



4
Close the valve and pump a little air into the growler to see if it is airtight. Opening the valve should release the pressurized air. Try it with a little water -- don't waste your beer!



5
Adjust the valve's closing pressure set screw if necessary -- usually no adjustment is needed.



6
Perfect for serving beer, the tapping device is designed to be interchangeable on all of our flip-top growler models.

Visit toteglass.com for more information!

Tote Glass, Inc. • P.O. Box 1924, Wilmington, NC 28402 • 910-515-4187 Fax: 910-251-0384 • toteglass.com

Copyright © 2018 Tote Glass, Inc. All rights reserved. Rev. 9-24-2018